
Django Act As Auth Documentation

Release 0.1.3

Paessler AG

Nov 27, 2017

Contents

1	Quickstart	3
2	Extension points	5
2.1	Authentication Backends	5
2.2	Views	5
2.3	Forms	6
2.4	Other	6
3	Supported Versions	7
3.1	Version Numbers	7
3.2	Django Versions Support Philosophy	7
3.3	Supported version of djactasauth	7
3.4	Supported Django and Python versions	7
4	License	9
5	Release Notes	11
5.1	0.3.0	11
5.2	0.2.1	11
5.3	0.2.0	11
5.4	0.1.7	11
5.5	0.1.6	12
5.6	0.1.5	12
5.7	0.1.4	12
5.8	0.1.3	12
5.9	0.1.2	12
5.10	0.1.1	12
5.11	0.1.0	13
6	Contributing	15
6.1	Reporting issues/improvements	15
6.2	Pull Requests	15
6.3	Setting up all Python versions	15
6.4	Code of Conduct	16
7	Authors	17

Django authentication backend that allows one to login as someone else (an existing Django user allowed to login) without having to know their password.

Great for customer support and testing scenarios!

Contents:

CHAPTER 1

Quickstart

Install djactasauth:

```
pip install djactasauth
```

Add it to your auth backends in settings:

```
import djactasauth
AUTHENTICATION_BACKENDS = (
    ...,
    'djactasauth.backends.OnlySuperuserCanActAsBackend',
    ...,
)
```

Configure the custom login view to take advantage of all the features in your `urls.py`:

```
from django.conf.urls import patterns, url
from djactasauth.views import act_as_login_view
from testapp.views import whoami

urlpatterns = patterns(
    '',
    url(r'^login/$', act_as_login_view, {}, 'login'),
)
```

Then you can log in with username `your_superuser_name/customer` and password `yourpassword`.

2.1 Authentication Backends

2.1.1 FilteredModelBackend

If a subclass of `djactasauth.backends.FilteredModelBackend` has a class or instance level `filter_kwargs` field, then those filters would be applied in the `FilteredModelBackend.get_user` method.

If there is no such field, it's ignored, and the behaviour is the same as its parent, `django.contrib.auth.backends.ModelBackend`.

An empty dictionary (`{}`) is also a valid value for filters, again, the behavior is the same as if no such field was specified.

2.1.2 ActAsBackend

You can have precise control over which user can act as which other kind of user, by subclassing `djactasauth.backends.ActAsBackend`, and describing your policy by overwriting the `can_act_as(self, auth_user, user)` method. For an example, see `djactasauth.backends.OnlySuperuserCanActAsBackend`.

`ActAsBackend` by default doesn't allow anyone to act-as, so there is no chance for misconfiguration.

2.2 Views

2.2.1 act_as_login_view

You can extend `djactasauth.views.act_as_login_view` through the standard kwargs, as you would extend `django.contrib.auth.views.login`, or you can create your own view method that eventually delegates to it - the same way this implementation does for Django's own :-)

2.3 Forms

2.3.1 `get_login_form`

```
djactasauth.views.get_login_form
```

This is used by `djactasauth.views.act_as_login_view`. On the one hand, it backports a Django 1.6 feature to 1.5 (pass in `request` as an argument to the form), and if needed, it mixes in `djactasauth.forms.InitialValuesFromRequestGetFormMixin`, so the username can be prefilled for act-as-auth links from the GET request.

2.3.2 `InitialValuesFromRequestGetFormMixin`

`djactasauth.forms.InitialValuesFromRequestGetFormMixin` is a Form mixin, which - given one of its super's has initialized the form's `self.request`, will get through `self.request.GET`, and copy over the values to `self.initial` - unless `self.initial` already has a value for the given field names you declared in your class's `query2initial` property (tuple).

This is needed for a feature here, but you might find it useful in other parts of your code too :-)

2.4 Other

2.4.1 `djactasauth.util.act_as_login_url`

Convenience method to encapsulate how the act as auth username should be constructed from the two usernames.

Supported Versions

3.1 Version Numbers

The project is versioned in the spirit of [Semantic Versioning](#). Note however that currently it's pre 1.0, thus *minor* version changes can be backwards incompatible. I.e.: 0.1.3 and 0.1.2 are compatible, but 0.2.0 and 0.1.3 are not.

3.2 Django Versions Support Philosophy

The project aims to support the versions Django itself supports.

3.3 Supported version of djactasauth

The project itself has only a single supported version, that is the latest stable release.

I.e.: bugfixes are not backported, i.e.: if the current stable release is 1.2.3, but the bug applies to all versions since 0.1.2, the bug will only be fixed in 1.2.4.

3.4 Supported Django and Python versions

See `tox.ini`.

`envlist = py{27,34,35}-django110, py{27,34,35,36}-django111,`

CHAPTER 4

License

Copyright (c) 2016, Paessler AG All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of djactasauth nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

5.1 0.3.0

- drop support for deprecated python and django versions
- conform to latest flake8

5.2 0.2.1

- bugfix: #12 - won't crash if username contains multiple act as auth sepchars (e.g.: admin/user/ (note the trailing slash)
- bugfix: #13 - wrapping `act_as_auth_view` in `sensitive_post_parameters`

5.3 0.2.0

- BACKWARDS INCOMPATIBLE: not inheriting from `ModelBackend`, but rather working in addition to the existing `settings.AUTHENTICATION_BACKENDS`
- BACKWARDS INCOMPATIBLE: only one act-as-auth backend can be configured for `settings.AUTHENTICATION_BACKENDS`

5.4 0.1.7

- add support for Django 1.11 and thus python 3.6

5.5 0.1.6

- add support for Django 1.10

5.6 0.1.5

- fix description on <https://pypi.python.org>

5.7 0.1.4

- first public release to pypi
- fixed `README.rst` to look OK on <https://pypi.python.org>

5.8 0.1.3

- explicitly add support for Django 1.6 and 1.7
- use Django's own bundled `six` instead of installing the external version
- explicitly add support for Django's own supported Python version, i.e.: Python 3.3 and 3.5 too (dropped 3.2 support as the travis build failed during setup)

5.9 0.1.2

- introduce
 - `act_as_login_view`
 - `act_as_login_url`
 - `get_login_form`
 - `InitialValuesFromRequestGetFormMixin`as part of the public api
- “backport” to Django 1.5: `authentication_form` has `request` even on POST
- can prefill username from query string
- bugfix: when user to act as is `None`, don't crash the process (e.g.: when `can_act_as` checked some property of the user, thus generating an `AttributeError`)

5.10 0.1.1

- bugfix: `ActAsModelBackend.is_act_as_username` used to fail when `username` argument was `None`, now it returns `False`
- explicitly regression testing for login redirecting to value provided in `REDIRECT_FIELD_NAME`
- bugfix: `setup.py` now lists its dependencies (and added `six`)

5.11 0.1.0

- initial release
- supports Django 1.5, 1.8 and 1.9 on python 2.7 and 3.4
- introduce `FilteredModelBackend`, `ActAsModelBackend`, and `OnlySuperuserCanActAsModelBackend`

As an open source project, we welcome contributions.

The code lives on [github](#).

6.1 Reporting issues/improvements

Please open an [issue on github](#) or provide a [pull request](#) whether for code or for the documentation.

For non-trivial changes, we kindly ask you to open an issue, as it might be rejected. However, if the diff of a pull request better illustrates the point, feel free to make it a pull request anyway.

6.2 Pull Requests

- for code changes
 - it must have tests covering the change. You might be asked to cover missing scenarios
 - the latest `flake8` will be run and shouldn't produce any warning
 - if the change is significant enough, documentation has to be provided
- if you are not there already, add yourself to the [Authors](#) file

6.3 Setting up all Python versions

```
sudo apt-get -y install software-properties-common
sudo add-apt-repository ppa:fkruhl/deadsnakes
sudo apt-get update
for version in 3.4 3.5 3.6; do
    py=python$version
```

```
sudo apt-get -y install ${py} ${py}-dev
done
```

6.4 Code of Conduct

As it is a Django extension, it follows [Django's own Code of Conduct](#). As there is no mailing list yet, please just email one of the main authors (see `setup.py` file)

CHAPTER 7

Authors

- Paessler AG <https://www.paessler.com>
- Peter Zsoldos <http://zsoldosp.eu>
- Kai Richard König
- Michael Zeidler

CHAPTER 8

Indices and tables

- `genindex`
- `search`